ASKO Logic Dishwasher

D5624XXLS

Type: Built-in
Colors: TouchProof™ stainless steel

PERFORMANCE
Capacity: 14 place settings
Noise level 50 dB(A)
7Spray™ system
PowerZone™ Pots & Pans, PowerZone™ Cutlery

PROGRAMS

Heavy	Super Quick	Daily
Quick	Rinse & Dry	Delicate
Eco	Rinse & Hold	Normal

Super Quick program in 15 minutes!

FEATURES
7 Temperatures, Condensation dry, Hidden control, LCD display, Front LED display, Integrated handle, Uses as little at 2.6 gals of water in Quick wash, Energy Star rated, 2 Plus 1 warranty

FLEXIRACKS™
Standard upper rack accommodates:
- 9" items
- Height-adjustable stemware shelf
- High-side design to protect dishes and glasses

Standard lower rack accommodates:
- 13 3/4" dishes

Cutlery basket

Asko Appliances, Inc
PO BOX 940609 • Plano • Texas • 75094
Phone 800.898.1879
www.askousa.com

Art no: 6301709

PLANNING & DESIGN: XXL DISHWASHERS

D5434XXL, D5624XXL, D5634XXLHS, D5654XXLHS, D5894XXLHS

Unit Dimensions

	US	METRIC
HEIGHT:*	34 3/8″ – 36 ½″	873 – 927 mm
WIDTH:	24″	610 mm
DEPTH:	22 7/8″	581 mm
DEPTH W/ HANDLE (HS):	24 7/8″	632 mm
DEPTH W/DOOR OPEN:	49 ½″	1257 mm
WEIGHT:	106 lbs	48 kg

Technical Data

Electricity	120 V, 60 Hz, 15 Amp
Water pressure	4.2 – 140 psi
Heating element	1200 watt
Max loading	1300 watt



Cutout Dimensions

	US	METRIC
HEIGHT:*	34 3/8″ – 36 ½″	873 – 927 mm
WIDTH:	24″	610 mm
DEPTH:	24″	610 mm

The electrical and water supplies should enter through the area indicated by the shaded area. Preferably, they should come through the right side of the machine. The access hole must be round and smooth and no bigger than 1 ½″ (38 mm) in diameter.

* ***Total height can be reduced by ½″ by removing upper trim.***



Specifications are subject to change without notice. See installation instructions for additional details.